



## CLAIM AMENDMENTS

1. (Original) An adapter for use in mounting an ancillary unit in an engine block which has at one end a lateral flange (10) formed with an aperture for mounting of the ancillary unit, the adapter comprising a casing (112) for mounting on the end face of the engine to overlies the aperture, which casing (112) is provided with an O-ring (130) for effecting a seal between the casing (112) and the aperture in the lateral flange (10) of the engine, and  
characterised in that the casing (112) has a larger diameter portion separated by a shoulder from a portion of reduced diameter, a retaining sleeve (132) being axially slidable over the reduced diameter portion of the casing thereby holding the O-ring (130) captive between the axial end of the retaining sleeve (132) and the shoulder.
2. (Original) An adapter according to claim 1, characterized in that the adapter further comprises a shaft (116) journaled in the casing (112), a formation (122) at one end of the shaft (116) to enable the shaft (116) to be coupled to the input shaft of the ancillary unit and a cog (120) solid with the opposite end of the shaft (116) for meshing with an engine driven gear.
3. (Original) An adapter according to claim 2, characterized in that the part of the drive shaft (116) engaged by the cog (120) has the same diameter as the part journaled in the casing (112).
4. (Original) An adapter according to claim 3, characterized in that the drive shaft (116) is formed as a hollow shaft.
5. (Original) An adapter according to claim 4, characterized in that an internally splined coupling is formed by broaching one end of the shaft (116).
6. (Original) An adapter according to claim 5, characterized in that an oil passage is provided to open into the hollow shaft (116) to provide oil for lubricating one of the thrust bearing surfaces (120a) of the cog (120).

7. (Original) A drive adapter according to claim 6, characterized in that the retaining sleeve (132) is held in position by the ancillary unit.

8. (Original) A drive adapter according to claim 7, characterized in that, prior to the mounting of the ancillary unit, a temporary cover plate (134) is operable to hold the retaining sleeve (132) in position.

9. (Original) A drive adapter according to claim 8, characterized in that the temporary cover plate (134) is held by means of bolts (136) that engage in the mounting holes for the ancillary unit.

10. (Currently Amended) A method of replacing an O-ring seal of an adapter as claimed in claim 1 ~~any preceding claim~~, which comprises the steps of:

- removing the ancillary unit from the adapter,
- sliding the retaining sleeve (132) off the reduced diameter portion of the casing (112),
- extracting the O-ring seal (130) from the gap between the casing (112) and the surrounding aperture in the engine lateral flange (10),
- fitting a new O-ring (130) over the reduced diameter portion of the casing (112),
- sliding the retaining sleeve (132) on to the reduced diameter portion of the casing (112) to push the new O-ring (130) towards the shoulder defined by the casing (112), and
- mounting the ancillary unit on the adapter so as to compress the new O-ring (130) between the retaining sleeve (132) and the shoulder.